IN THE CLAIMS:

The following listing of claims will replace all prior listings of claims in the application:

 (Currently Amended): A dedicated, hardware-based Physics Processing Unit (PPU), comprising:

a vector processor adapted to perform multiple, parallel floating point operations to generate physics data, wherein the multiple, parallel floating point operations are specified by a very long instruction word (VLIW) that is issues to the vector processor; and

a data communication circuit adapted to communicate the physics data to a host Central Processing Unit (CPU).

- (Currently Amended): The PPU of claim 1, wherein the host comprises a Central Processing Unit (CPU), and the PPU further comprises:
- a PPU Control Engine (PCE) receiving commands from the CPU and controlling communication the physics data from the PPU to the host.
- (Original): The PPU of claim 2, wherein the PPU further comprises: an external memory and an internal memory; and
- a Data Movement Engine (DME) controlling the movement of data between the external memory and the internal memory in response to instructions received from the PCE.
- 4. (Original): The PPU of claim 3, further comprising:
- a Floating Point Engine (FPE) performing multiple, parallel floating point operations on data stored in the internal memory.
- 5. (Original): The PPU of claim 4, wherein the internal memory is operatively connected to the DME, and further comprising:
- a high-speed memory bus operatively connecting an external high-speed memory to at least one of the DME and the FPE.

- (Original): The PPU of claim 5, wherein the internal memory comprises multiple banks allowing multiple data threading operations.
- (Original): The PPU of claim 3, wherein the PCE comprises control and communication software stored in a RISC core.
- 8. (Original): The PPU of claim 5, wherein the internal memory comprises first and second banks, and wherein the DME further comprises:
 - a first unidirectional crossbar connected to the first bank;
 - a second unidirectional crossbar connected to the second bank; and,
- a bi-directional crossbar connecting first and second crossbars to the external high-speed memory.
- (Currently Amended): A dedicated, hardware-based Physics Processing Unit (PPU) connected within a system, to a Contral Processing Unit (CPU) and comprising:
 - a Central Processing Unit (CPU):
 - an external memory storing data: and.
- a dedicated, hardware-based Physics Processing Unit (PPU) connected to the CPU and comprising an Application Specific Integrated Circuit (ASIC) implementing a vector processor adapted to perform multiple, floating point operations, wherein the multiple, parallel floating point operations are specified by a very long instruction word (VLIW) that is issues to the vector processor; and
- an external memory storing data, wherein the external memory is communicatively coupled to the PPU.
- 10. (Currently Amended): The PPU system of claim 9, wherein the system semprises further comprising a Personal Computer (PC); and wherein the PPU comprises an expansion board adapted for incorporation within the PC, the expansion board mounting the ASIC and the external memory.

- (Currently Amended): The PPU system of claim 10, further comprising circuitry enabling at least one data communications protocol between the PPU and CPU.
- (Currently Amended): The <u>PPU system</u> of claim 11, wherein the at least one data communications protocol comprises at least one protocol selected from a group of protocols defined by USB, USB2, Firewire, PCI, PCI-X, PCI-Express, and Ethernet.
- (Currently Amended): The PPU system of claim 11, wherein the ASIC comprises a PPU Control Engine (PCE) receiving commands from the CPU and controlling data communications between the PPU and PC.
- 14. (Currently Amended): The PPU system of claim 13, wherein the ASIC further comprises:

an internal memory; and

- a Data Movement Engine (DME) controlling the movement of data between the external memory and the internal memory in response to instructions received from the PCE.
- 15. (Currently Amended): The PPU system of claim 14, further comprising: a Floating Point Engine (FPE) performing multiple, parallel floating point operations on data stored in the internal memory.
- (Currently Amended): The PPU system of claim 15, wherein the internal memory is operatively connected to the DME, and further comprising:
- a high-speed memory bus operatively connecting the external memory to at least one of the DME and the FPE.

- (Currently Amended): The PPU system of claim 16, wherein the internal memory comprises multiple banks allowing multiple data threading operations.
- 18. (Currently Amended): The PPU <u>system</u> of claim 17, wherein the internal memory further comprises:

an Inter-Engine memory transferring data between the DME and FPE.

- 19. (Currently Amended): The PPU system of claim 18, wherein the internal memory further comprises:
 - a Scratch Pad memory.
- (Currently Amended): The <u>PPU system</u> of claim 14, further comprising a
 command packet queue transferring command packets from the PCE to the DME.
- 21. (Currently Amended): The PPU system of claim 15, wherein the FPE comprises a plurality of Vector Floating-point Units.
- 22. (Currently Amended): The PPU system of claim 21, wherein at least one of the command packets defines a vector length of variable length.
- (Currently Amended): The PPU system of claim 15, wherein the DME comprises a plurality of Memory Control Units (MCUs) and a Switch Fabric connecting the MCUs to the external memory; and,

wherein the FPE comprises a plurality of Vector Processing Engines (VPEs) receiving date from at least one of the MCUs via a VPE bus.

24. (Currently Amended): The PPU system of claim 23, wherein each Vector Processing Engine (VPE) comprises a plurality of Vector Processing Units (VPUs) receiving data from the VPE bus.

25. (Currently Amended): The PPU system of claim 24, wherein each VPU comprises:

a dual bank[[.]] Inter-Engine Memory (IEM) receiving data from the VPE bus; one or more data registers receiving date from the IEM under the control of an associated Load/Store Unit; and

an Execution Unit performing parallel floating point operations.

- (Currently Amended): The PPU system of claim 23, wherein at least one command packet received from the PCE defines a vector length of variable length.
- 27. (Currently Amended): The PPU system of claim 23, wherein the Switch Fabric comprises at least one crossbar circuit.
- 28. (Currently Amended): The PPU system of claim 24, wherein each VPU is dvnamically re-configurable.